## 11 NARRATIVE 13 BASIS OF BEARING NOTE: This survey was done at the request of John Manwell of Forest Capital. The purpose of the survey is to monument selected corners within Section 24 and the GLO Corners For monumentation information, see The South line of Section 25, Township 3 North, controlling the subdivision of the section. The metes and bounds tract near the monumentation records filed separately Range 39 East of the Willamette Meridian being Southwest corner of the section was also monumented. The line from the West 1/4 South 89°57'00" East, as per Union County Survey No. 14-85 corner of Section 25 to the West 1/4 corner of Section 24 was retraced by County Surveyor S.B. Morgan during the road survey for Bowman Loop. I use his retracement and place the monuments at the centerline of the road, as called for in the road survey, and by deeds recorded in deed volume 111, pages 246 through 254, which granted the SCALE: 1"=1000' right of way to the county. The West 1/4 corner of Section 25 was placed at the intersection of Bowman Loop and Moses Creek Lane. The Southwest corner and West 1/4 corner of Section 24 were placed at the centerline of Bowman Loop at the intersection of existing fence lines. I found an unrecorded brass plate marked as being the Southeast corner of Section 24. Due to harmony, I accept this monument for the section corner. The Northwest corner of Section 24 was placed in an existing North-South fence line at proportionate distance North and South. The fence line is at (North) 0°15°26"E the distance called for in the original notes from an existing creek to the East. I therefore accept the East-West position of the fence as being the best available evidence 2613.01 (40 ch) of the original corner placement. The remaining corners not found were placed by proportionate measurement and the section subdivided according to the BLM Manual of Surveying Instructions. The metes and bounds tract was placed at the record deed calls using the subdivision of the section as established. The fences in this area are relatively Z harmonious with the tract as shown. I find no other unusual conditions on this survey. (80.60 ch) (N89°53'W) 13 15 (N89°56'W) 18 S 89°57'45"E (80.08 ch) 13 5431.06 N 89°28'33"W 5145.57 2715.53 (40.30 ch) 1357.77 24 2572.77 2572.78 (40.04 ch) 1357.76 1357.76 22 19 o lärorest (40.04 ch) 24 Capital 2715.53 (40 ch) **2613.02** (40.30 ch) REFERENCE MATERIAL N 89°51'38"W 2703.80 S 89°48'19"E GLO Contract Number 437 by Rufus S. Moore, dated June 3, 1882 1351.90 80 GLO Contract Number 498 by Frank W. 1339.56 019,57 (North) 0°04'. Campbell, dated May 15, 1884 Union County monumentation records $\theta$ 3 Survey Number 49-71 Survey Number 77-71 Survey Number 14-85 Z S-5 89°45'29"E 5429.73 Number 2692 08 DEED REFERENCES 1346.04 1340.5 1340.5 18707est 1346.04 2737.65 Volume 111 Pages 246 through 254 Loop Volume 144 Page 635 (40 ch) **2638.46** Microfilm Number 25113 capital. Microfilm Number 39608 **0°06°19"E** [North] Microfilm Number 44823 1319.23 Road Microfilm Number 143836 Microfilm Number 20045408 0.01,30"E S89°48'19"E 2679.12 1339.56 1339.56 Bowman CountyZ Found 5/8" iron pin set by Survey Number 77-71 Found unrecorded brass plate set in concrete monument 24 19 319.75 **(** Found 2" aluminum monument as per 2759.85 monumentation records (unless otherwise noted) N 89°47'31"W 89°51'11"W 2666.16 89°51'11"W 1333.08 25 30 **(** Set 2 1/2"x30" aluminum monument from original (40.10 ch) **★** 297.00 573.94 GLO evidence (N89\*51'W) (80.20 ch) 25 432.12 132 ≥ N 89°51'11"W Set 5/8"x30" "copper clad" iron pin with 2 1/2" 0°26'37"E brass cap in Water Valve box from existing corner accessories ((N 1'W)) (North) 1°13'34" N 89°51'11"W 0 Set 2 1/2"x30" aluminum monument at position 462.12 determined by survey Scale 1" = 300'2 Set 5/8"x30" "copper clad" iron pin with 2 1/2" Z brass cap at position determined by survey Set 5/8"x30" iron pin with 2 1/2" aluminum cap $\oplus$ Detail of the SW 1/4 of the SW 1/4 of Section 24 at position determined by survey Set 5/8"x30" iron pin with plastic cap marked 0 "BGB SURVEY MARKER" Record information of GLO Contract Number 437 by BAGETT, GRIFFITH & BLACKMAN Rufus S. Moore [North] **0°04'01"E** UNION COUNTY 2006 Adams Avenue, LaGrande, Oregon **2631.16** [40 ch] 0°32'41 REGISTERED SURVEYOR Record information of GLO Contract Number 498 by Map of Survey **PROFESSIONAL** 2640. Frank W. Campbell LAND SURVEYOR Monumentation within Section 24, 9/14/05 Date Received Record information of deed volume 111, pages 246 Township 3 North, Range 39 East (( )) through 254 Z of the Willamette Meridian Z OREGON UNION COUNTY, OREGON Record information of Survey Number 14-85 RICK G. ROBINSON SURVEYED FOR Forest Capital Set steel fence posts on line at approximately 250 {S89°57'00"E} 26 *{5323.36}* **5321.16** 2219 25 *30* S 89°57'00"E SURVEYED BY R.G.R. 8/05 File No. 017-2005 Renewal Date: Dec. 31, 2006 35 36 Existing fence line 36 31 Scale: As Shown Drawn by: R.G.R. 9/05