

RECORD OF SURVEY

05
1888

Township

Range

Union County, Oregon.

- | Date | Time | Description |
|------|------|---|
| 20 | 50 | Set Temporary 1/16 corner |
| 36 | 50 | Intersect E 1/4 NW line at center |
| 50 | 50 | The 1/4 Sec corner bet Sec 23 & 26
Thence South |
| 44 | 50 | Set into Sec 26 |
| 62 | 25 | Set Stone for 1/16 corner in center of Sec 26 |
| 50 | 50 | The 1/4 Sec corner bet Sec 26 & 35 -
Thence East |
| 20 | 50 | Set Post in mound Stone for 1/8 corner |
| | | The 1/4 Sec corner bet Sec 23 & 26 Thence West over 20° E |
| 52 | 15 | Intersect N 1/4 S line 692 lbs North of corner to Sec 22-23-26 & 27
N 80° 35' E on line |
| 52 | 38 | The 1/4 Sec corner bet Sec 23 & 26
The corner to 34 & 35 on Standard line
Thence West over 20° 15' E |
| 40 | 15 | The 1/4 Sec corner on South boundary Sec 34
Thence North through Sec 34 |
| 20 | 50 | Set Temporary 1/16 corner |
| 40 | 50 | Set Temporary center Sec 34 |
| 50 | 40 | Intersect North Edge Sec 34 45 lbs East of 1/4 Sec corner bet Sec 27 & 34
The 1/4 Sec corner bet Sec 34 & 35 -
Thence West through Sec 34 |
| 20 | 50 | Set Temporary 1/16 corner |
| 40 | 36 | Intersect N 1/4 S line |
| 80 | 20 | The 1/4 Sec corner bet Sec 33 & 34 |
| 99 | 84 | Set Stone in mound of Stone for center |
| 60 | 02 | Set Stone for center E 1/2 Sec 34
Thence South |
| 39 | 90 | Set Stone in mound of Stone for center S E 1/4 Sec 34 |

J. W. Ferris, Deputy County Surveyor